

# SAFETY DATA SHEET

Version  
3.0 Revision Date  
09/04/2017

## 1. PRODUCT AND COMPANY IDENTIFICATION

### 1.1 Product identifiers

Product name : Tantalum  
Brand : SAM  
  
CAS-No. : 7440-25-7

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

### 1.3 Details of the supplier of the safety data sheet

Company : Stanford Advanced  
Materials  
23661 Birtcher Dr.  
Lake Forest, CA 92630  
USA  
  
Telephone : +1 (949) 407-8904  
Fax : +1 (949) 812-6690

### 1.4 Emergency telephone number

Emergency Phone # : +1 (949) 407-8904

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable solids (Category 2), H228

Skin irritation (Category 2), H315

Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Warning

Hazard statement(s)

H228

Flammable solid.

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H335

May cause respiratory irritation.

Precautionary statement(s)

P210

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240

Ground/bond container and receiving equipment.

P241

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P261

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264

Wash skin thoroughly after handling.

P271

Use only outdoors or in a well-ventilated area.

|                    |                                                                                                                                  |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------|
| P280               | Wear protective gloves/ eye protection/ face protection.                                                                         |
| P302 + P352        | IF ON SKIN: Wash with plenty of soap and water.                                                                                  |
| P304 + P340 + P312 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.       |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P332 + P313        | If skin irritation occurs: Get medical advice/ attention.                                                                        |
| P337 + P313        | If eye irritation persists: Get medical advice/ attention.                                                                       |
| P362               | Take off contaminated clothing and wash before reuse.                                                                            |
| P370 + P378        | In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.                                             |
| P403 + P233        | Store in a well-ventilated place. Keep container tightly closed.                                                                 |
| P405               | Store locked up.                                                                                                                 |
| P501               | Dispose of contents/ container to an approved waste disposal plant.                                                              |

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances

|                  |                |
|------------------|----------------|
| Formula          | : Ta           |
| Molecular weight | : 180.95 g/mol |
| CAS-No.          | : 7440-25-7    |

#### Hazardous components

| Component              | Classification                                                                | Concentration |
|------------------------|-------------------------------------------------------------------------------|---------------|
| <b>Tantalum powder</b> |                                                                               |               |
|                        | Flam. Sol. 2; Skin Irrit. 2; Eye Irrit. 2A; STOT SE 3; H228, H315, H319, H335 | 90 - 100 %    |

For the full text of the H-Statements mentioned in this Section, see Section 16.

### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

##### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

##### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

##### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

##### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

##### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

---

## 5. FIREFIGHTING MEASURES

### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

### 5.2 Special hazards arising from the substance or mixture

No data available

### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

### 5.4 Further information

Use water spray to cool unopened containers.

---

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

### 6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal. Contain spillage, pick up with an electrically protected vacuum cleaner or by wet-brushing and transfer to a container for disposal according to local regulations (see section 13).

### 6.4 Reference to other sections

For disposal see section 13.

---

## 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs.

Provide appropriate exhaust ventilation at places where dust is formed. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Keep in a dry place.

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

## 8. EXPOSURE CONTROLS/PERSONAL

### PROTECTION 8.1 Control parameters

#### Components with workplace control parameters

| Component       | CAS-No.   | Value                                                                                                  | Control parameters | Basis                                                                            |
|-----------------|-----------|--------------------------------------------------------------------------------------------------------|--------------------|----------------------------------------------------------------------------------|
| Tantalum powder | 7440-25-7 | TWA                                                                                                    | 5.000000 mg/m3     | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
|                 |           | TWA                                                                                                    | 5.000000 mg/m3     | USA. ACGIH Threshold Limit Values (TLV)                                          |
|                 | Remarks   | Upper Respiratory Tract irritation<br>Adopted values or notations enclosed are those for which changes |                    |                                                                                  |

|  |  |                                                                 |                 |                                                                                         |
|--|--|-----------------------------------------------------------------|-----------------|-----------------------------------------------------------------------------------------|
|  |  | are proposed in the NIC<br>See Notice of Intended Changes (NIC) |                 |                                                                                         |
|  |  | TWA                                                             | 5.000000 mg/m3  | USA. NIOSH Recommended Exposure Limits                                                  |
|  |  | ST                                                              | 10.000000 mg/m3 | USA. NIOSH Recommended Exposure Limits                                                  |
|  |  | TWA                                                             | 5.000000 mg/m3  | USA. NIOSH Recommended Exposure Limits                                                  |
|  |  | ST                                                              | 10.000000 mg/m3 | USA. NIOSH Recommended Exposure Limits                                                  |
|  |  | TWA                                                             | 5.000000 mg/m3  | USA. NIOSH Recommended Exposure Limits                                                  |
|  |  | ST                                                              | 10.000000 mg/m3 | USA. NIOSH Recommended Exposure Limits                                                  |
|  |  | TWA                                                             | 5 mg/m3         | USA. NIOSH Recommended Exposure Limits                                                  |
|  |  | ST                                                              | 10 mg/m3        | USA. NIOSH Recommended Exposure Limits                                                  |
|  |  | PEL                                                             | 5 mg/m3         | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |

## 8.2 Exposure controls

### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

### Personal protective equipment

#### Eye/face protection

Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

#### Body Protection

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

- |                                 |                                          |
|---------------------------------|------------------------------------------|
| a) Appearance                   | Form: powder<br>Colour: light grey       |
| b) Odour                        | No data available                        |
| c) Odour Threshold              | No data available                        |
| d) pH                           | No data available                        |
| e) Melting point/freezing point | Melting point/range: 2,996 °C (5,425 °F) |

- |    |                                              |                                                                    |
|----|----------------------------------------------|--------------------------------------------------------------------|
| f) | Initial boiling point and boiling range      | 5,425 °C (9,797 °F)                                                |
| g) | Flash point                                  | Not applicable                                                     |
| h) | Evaporation rate                             | No data available                                                  |
| i) | Flammability (solid, gas)                    | The substance or mixture is a flammable solid with the category 2. |
| j) | Upper/lower flammability or explosive limits | No data available                                                  |
| k) | Vapour pressure                              | No data available                                                  |
| l) | Vapour density                               | No data available                                                  |
| m) | Relative density                             | 16.69 g/cm <sup>3</sup>                                            |
| n) | Water solubility                             | insoluble                                                          |
| o) | Partition coefficient: n-octanol/water       | No data available                                                  |
| p) | Auto-ignition temperature                    | 300 °C (572 °F)                                                    |
| q) | Decomposition temperature                    | No data available                                                  |
| r) | Viscosity                                    | No data available                                                  |
| s) | Explosive properties                         | No data available                                                  |
| t) | Oxidizing properties                         | No data available                                                  |

## 9.2 Other safety information

No data available

---

## 10. STABILITY AND REACTIVITY

### 10.1 Reactivity

No data available

### 10.2 Chemical stability

Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

No data available

### 10.4 Conditions to avoid

Heat, flames and sparks.

### 10.5 Incompatible materials

No data available

### 10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Tantalum Oxides

Other decomposition products - No data available

In the event of fire: see section 5

---

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

#### Acute toxicity

LC50 Oral - Mouse - 595 mg/kg

Inhalation: No data available

Dermal: No data available

No data available

**Skin corrosion/irritation**

No data available

**Serious eye damage/eye irritation**

No data available

**Respiratory or skin sensitisation**

No data available

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**Reproductive toxicity**

No data available

No data available

**Specific target organ toxicity - single exposure**

No data available

**Specific target organ toxicity - repeated exposure**

No data available

**Aspiration hazard**

No data available

**Additional Information**

RTECS: Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

---

**12. ECOLOGICAL INFORMATION****12.1 Toxicity**

No data available

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

**12.6 Other adverse effects**

No data available

---

**13. DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods****Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

**Contaminated packaging**  
Dispose of as unused product.

---

## 14. TRANSPORT INFORMATION

### DOT (US)

UN number: 3089      Class: 4.1      Packing group: II  
Proper shipping name: Metal powders, flammable, n.o.s.  
Reportable Quantity (RQ):  
Poison Inhalation Hazard: No

### IMDG

UN number: 3089      Class: 4.1      Packing group: II      EMS-No: F-G, S-G  
Proper shipping name: METAL POWDER, FLAMMABLE, N.O.S.

### IATA

UN number: 3089      Class: 4.1      Packing group: II  
Proper shipping name: Metal powder, flammable, n.o.s.

---

## 15. REGULATORY INFORMATION

### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard

### Massachusetts Right To Know Components

Tantalum powder

CAS-No.  
7440-25-7

Revision Date  
1993-04-24

### Pennsylvania Right To Know Components

Tantalum powder

CAS-No.  
7440-25-7

Revision Date  
1993-04-24

### New Jersey Right To Know Components

Tantalum powder

CAS-No.  
7440-25-7

Revision Date  
1993-04-24

### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

---

## 16. OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3.

|             |                                                  |
|-------------|--------------------------------------------------|
| Eye Irrit.  | Eye irritation                                   |
| Flam. Sol.  | Flammable solids                                 |
| H228        | Flammable solid.                                 |
| H315        | Causes skin irritation.                          |
| H319        | Causes serious eye irritation.                   |
| H335        | May cause respiratory irritation.                |
| Skin Irrit. | Skin irritation                                  |
| STOT SE     | Specific target organ toxicity - single exposure |

### HMIS Rating

|                        |   |
|------------------------|---|
| Health hazard:         | 2 |
| Chronic Health Hazard: |   |
| Flammability:          | 3 |

Physical Hazard 3

**NFPA Rating**

Health hazard: 2

Fire Hazard: 3

Reactivity Hazard: 3

**Further information**

This material safety data sheet is offered solely for your information, consideration, and investigation. Stanford Advanced Materials provides no warranties, either express or implied, and assumes no responsibility for the accuracy or completeness of the data contained herein.